

# MENA Desalination Projects

*April 2021*



# Company Background

True North Venture Partners acquires established innovative ceramic technology, launches **Nanostone Water**

Beta product launched and initial demonstration projects deployed

First commercial installations; microelectronics, boiler feed

Largest industrial and drinking water installations in operation



Expand into Desalination

R&D advances to prototype and alpha product field testing; pilot production line upgraded

Commercial product development and qualification and commercial production line design and retrofit

First commercial drinking water installations

Global expansion of both business and resources



- HQ Waltham, MA
- Manufacturing Halberstadt, GER
- Sales & Engineering Offices



**Halberstadt, Germany: Automated production line with largest ceramic membrane capacity in the world.**




# Manufacturing and Technical Center – Halberstadt, Germany



*Co-locating R&D, manufacturing, and administrative staff also helps drive increased **collaboration** and **innovation***

*Nanostone's advanced manufacturing plant is home to the **largest ceramic membrane production capacity** in the world*






Innovation in design  
improving performance



- Nanostone Water is leading the industry with our **innovative ceramic design**
- We've optimized our product and production process to **optimize yield** and **lower capital costs** and **operating costs**
- The ceramic surface coating also enables tight pore size distribution, resulting in **improved performance and reliability**



# Nanostone Module (Universal Design)



262 ft<sup>2</sup>/24.3 m<sup>2</sup> area  
 $\alpha$ - Al<sub>2</sub>O<sub>3</sub> ceramic membrane

Inside-Out Filtration  
Dead-end operation



Permeate /  
Backwash



Overall vessel height 75.5 in, Dia  
9.8 in, Shipping weight 95 kg

7 Bar rated FRP  
vessel

Super Duplex 2507  
Permeate Port



# Nanostone Ceramic Membranes – Key Features and Benefits

---



- Operates at **very high flux** (3–6 times higher than PUF)
- Higher **recovery** than polymeric MF/UF
- Runs stably at **high solids loading**, especially inorganics
- Dosing of **coagulant** is well-tolerated and even **improves performance**
- Stable operation **without pre-treatment** (ceramic UF eliminates the need for clarifiers and multi-media filters which are often used before polymeric UF)
- **CapEx-competitive** on a system-to-system basis with compact footprint
- **pH resistance** from 1–13 in cleaning, 2–12 in operation
- **Operational temperature** 33 –113 °F (0.5 –45 °C)
- Depending on application, membranes may be **guaranteed for up to 20 years**
- **Robust and reliable** (no fibers to break or repair)
- **Lower operational complexity and cost** (no air scour required, fewer chemicals and electricity when removing treatment steps, higher water recovery)

# Nanostone Ceramic Membranes Installed Capacity 2017-2021

---



- Total installed capacity since 2017 is **307 MLD**
  - ✓ Municipal: **85 MLD** (all retrofits of the existing PUF membranes)
  - ✓ Industrial: **222 MLD** (majority greenfield, 30% retrofits)
- Biggest industrial plant **48 MLD** (Inner Mongolia, China), coal mining
- Biggest municipal plant **54 MLD** (Canyon Regional Water Authority, TX, US), drinking water
- Relatively rapid growth installed capacity mainly caused by:
  - ✓ Failing polymeric membrane (integrity and fouling issues)
  - ✓ Advantages of ceramic ultrafiltration membranes
  - ✓ Same “simple” or standard infrastructure makes it easy to switch to ceramic UF membrane (or back)
- This polymeric retrofit capability makes the Nanostone ceramic ultrafiltration membrane unique in the market

# Desalination pretreatment issues

---

- Seawater challenges
  - Algal blooms / red tide
  - High variability – tidal effect
  - Dissolved organic content (DOC) – such as Transparent Exopolymer Particles (TEP)
- Polymeric Membranes
  - Implemented in many plants beginning ~15 years ago to address concerns with conventional treatment
  - Suitable for surface water but desalination plants have struggled
    - Permit pass-through of DOC leading to excessive fouling of RO
    - Unable to maintain capacity even at extremely low design flux
    - Susceptible to fiber breaking, therefore breakthrough






# Desalination pretreatment today

---

- Dissolved Air Flotation (DAF) now being added ahead of polymeric membranes
  - Adds significant capital cost
  - Requires large footprint
  - High operating cost associated with chemical dosing and sludge removal
- “State-of-the-art today is DAF and multi-media filtration”
  - Leading seawater utility manager at Global Water Summit in April 2019
  - Polymeric membranes have failed
- DAF + MMF have their own problems
  - Expensive
  - Footprint
  - Significant risk of solids carry-over

# Scheme Optimization & Lowest pretreatment Costs-SeaWater Desalination



- “Enhanced” Coagulation for Algae/DOC removal
- Direct seawater filtration
- No fibers = no air blower/scouring

# Nanostone's ceramic membrane and module ideally suited for desalination pre-treatment

---

- Membrane and module are sea water resistant
- Large channels (2.4 mm) can hold a large amount of solids and algae
- Minimal pre-treatment (coagulation only) is necessary to function optimally
  - no need for Dissolved Air Flootation (DAF) or other forms of clarification,
  - saving space and complexity while improving reliability
- Can operate optimally with coagulation removing organics significantly improving downstream RO operations
  - many membrane systems avoid coagulation placing burden on downstream processes
- High fluxes (> 200 l/mh) can be achieved reducing foot print
  - many desalination plants are located in urban areas land is a premium
- Rigorous cleaning can be achieved with high flow backwashing and chemicals



# Overview or Pilot at Tuas (Singapore PUB)



*Tuas derives its intake 1.4 km off-shore*

## Objectives

- Stable UF-performance at economical feasible flux
- Highest possible NOM/DOC removal for downstream RO
- Absolute filtration for SS (low Turbidity, SDI)

## Pre-treatment

- Continuous 5 days 2 ppm NaOCl dose, +6 ppm shock dose for 2 days (8ppm)
- Sieve 20 mm
- Rough screen 2mm (other MF/UF pilots on site have a 400 $\mu$ m or finer screen)
- In-line coagulation with FeCl<sub>3</sub>, pH-control and 1-3 minute contact time

## Logistics

- Trial of 6 months
  - 3 months optimization
  - 3 months longer-term monitoring

# Status of Pilot at Tuas (Singapore PUB)

---

## Jar Testing

- Find initial coagulant dose and pH-range (done)
- 

## Commissioning

- Delayed by Covid-19 circuit breaker events
- 

## In-line coagulation

- Initial optimization, 4 weeks (done)
  - Confirm jar tests in a continuous process
  - Find optimum pH (done)
- 

## Optimization

- Establish critical flux, 4 weeks (done)
  - Establish filtration time or optimum load L/m<sup>2</sup>, 2 weeks (done)
  - Establish CEB frequency, 3 weeks (done)
- 

## Long-Term Operation

- Confirm/validate optimum operation, 12 weeks








# Technical background/research at TUAS (PUB) – Optimizing ILC

---


- Based on theory expectations for pH 5 are:
  - Closer to “Enhanced” coagulation
  - Higher removal percentage DOC (humic fraction)
  - Some irreversible fouling caused by charged matter
  - Charged metal organic complexes formed
- Based on theory expectations for pH 7 are:
  - Closer to “Sweep” flocculation
  - Lower removal rate DOC (mainly HMW fraction)
  - Less irreversible fouling caused by formation of uncharged  $\text{Fe}(\text{OH})_3$




### Normalized TMP at 20°C




### Fouling rate within a filtration cycle





### Fouling rate within a filtration cycle



### Backwash Efficiency



# Long Term Operation






# Estimated CIP Frequency


- Flux – 250 l/mh with 90 mins filtration cycle
- CEB frequency – every 24 hours
- Operation period – 31st Dec 20 – 21st Jan 21 (22 days)
- Fouling rate – 1.1317 kPa/day
- CIP Frequency – 89 days

- Flux – 250 l/mh with 90 mins filtration cycle
- CEB frequency – every 24 hours
- Operation period – 19th Feb 20 – 15th Mar 21 (26 days)
- Fouling rate – 0.9327 kPa/day
- CIP Frequency – 107 days

TMP Increase Rate = 1.1317 kPa/day




TMP Increase Rate = 0.9327 kPa/day



- CIP frequency is calculated based on initial TMP = 50 kPa and TMP before CIP = 150 kPa



# Critical Flux Determination




- CIP Frequency:
- Fouling rate for 100 l/mh run = 0.2761 kPa/day (~360 days CIP frequency)
- Fouling rate for 150 l/mh run = 0.2951 kPa/day (~340 days CIP frequency)
- Fouling rate for 200 l/mh run = 2.4313 kPa/day (~45 days CIP frequency)
- Fouling rate for 250 l/mh run = 3.2266 kPa/day (~31 days CIP frequency)
- Fouling rate for 300 l/mh run = 4.6611 kPa/day (~22 days CIP frequency)

Fouling at higher flux mainly caused by BW efficiency loss  
300l/mh approached hydraulic limitation of system  
250 l/mh chosen to further optimize (stabilization)

# Backwash Frequency Optimization



# CEB Frequency Optimization



- No impact on performance during neap tide
- decreasing CEB-frequency has positive effect on stability!
- SS on the permeate side formed by CEB reformation

# Water Quality permeate

---

- Turbidity
  - Raw water turbidity is in the range of 2-14 NTU and filtrate turbidity is below 0.05 NTU most of the time (spiked after CEB or BW only).
- TOC, DOC and UVT
  - Raw water TOC and DOC are typically in the range of 1-3 mg/l
  - The TOC and DOC removal after filtration are around 30% at typical feed quality ranges and 50-70% at higher feed water concentrations.
  - The filtrate UVT is in average around 98%.
  - LC-OCD only feasible at raw water and coagulated water, permeate gave signals that were too low to interpreted on the LC-OCD
- $SDI_{15}$ 
  - Filtrate  $SDI_{15}$  are in average around 2. The  $SDI_{15}$  was higher during the high algae concentration season (Chlorophyll-a ~ 40 ppb).
- Iron
  - The filtrate total iron and dissolved iron are less than 0.0045 mg/l



# Summary of Testing and Conclusions

---

- Membrane operation is stable during algae blooms and tide events with *negligible impact on performance*
- Established operating parameters demonstrate economically attractive set points
  - Flux 250 lhm at 90 min filtration cycles
  - CEB after 15 FC cycles (approx. 1/day)
- Demonstrated, sustainable and stable flux means:
  - Reduced footprint
  - Reduced CAPEX
- Demonstrated operational set points mean:
  - Increased water production efficiency
  - Increased up time and lower OPEX
- A robust, reliable and cost effective solution for desalination pre-treatment

# Canyon Regional Water Authority – Lake Dunlap



Capacity	55 MLD
Source	Surface Water
Pre-treatment	Coagulated and Settled
Flux	365 LMH
Filtration. cycle	120 min

Canyon Regional Water Authority  
Retrofit of Koch PUF



# THANK YOU

## Nanostone Water

[www.nanostonewater.com](http://www.nanostonewater.com)

